

```

<comment>Extension to use when none can be determined from mappings</comment>
</param>
<param name="datastreamDefaultFilename" value="download">
<comment>Filename to use for datastream downloads when none can be determined from the
sources listed in datastreamFilenameSource.</comment>
</param>
<param name="datastreamExpirationLimit" value="300">
<comment>Controls the size of the datastream mediation hash by removing
entries outside the specified threshold. The value is specified in
seconds. Note this value must be greater than the limit specified for
the datastreamMediationLimit.</comment>
</param>
<param name="datastreamExtensionMappingRel" value="never">
<comment>Controls filename extension mapping when RELS-INT is used
as the source of the filename. Values are as above.</comment>
</param>
<param name="httpClientTimeoutSecs" value="20">
<comment>Number of seconds Fedora http client will wait for a connection before timing
out.</comment>
</param>
<param name="repositoryName" value="Fedora Repository">
<comment>Defines a human readable name for the Fedora server; default is
Fedora Repository.</comment>
</param>
<module role="org.fcrepo.server.security.Authorization"
class="org.fcrepo.server.security.DefaultAuthorization">
<comment>Builds and manages Fedora's authorization structure.</comment>
<param name="REPOSITORY-POLICY-GUITOOL-POLICIES-DIRECTORY" value="data/fedora-xacml-policies/repository-
policies-generated-by-policyguitool" isFilePath="true">
<comment>This parameter is for future use.</comment>
</param>
<param name="POLICY-SCHEMA-PATH" value="xsd/cs-xacml-schema-policy-01.xsd"/>
<param name="ENFORCE-MODE" value="enforce-policies"/>
<param name="VALIDATE-OBJECT-POLICIES-FROM-DATASTREAM" value="false"/>
<param name="XACML-COMBINING-ALGORITHM" value="com.sun.xacml.combine.OrderedDenyOverridesPolicyAlg"/>
<param name="VALIDATE-OBJECT-POLICIES-FROM-FILE" value="false"/>
<param name="VALIDATE-REPOSITORY-POLICIES" value="true"/>
<param name="REPOSITORY-POLICIES-DIRECTORY" value="data/fedora-xacml-policies/repository-policies"
isFilePath="true"/>
</module>
<module role="org.fcrepo.server.security.BackendSecurity"
class="org.fcrepo.server.security.DefaultBackendSecurity">
<comment>Description: Interface to the backend service security
configuration. This module initializes backend service security
information in the server by parsing the beSecurity configuration file.
This file is located in the distribution in
$FEDORA_HOME/dist/server/config/beSecurity.xml. The configuration file
is read once at server startup.</comment>
<param name="beSecurity_char_encoding" value="utf-8">
<comment>The character encoding used for the beSecurity
configuration file. The default is "utf-8". The value
specified must correspond to the character encoding used in the
beSecurity configuration file.</comment>
</param>
<param name="beSecurity_validation" value="false">
<comment>Controls whether beSecurity config file is validated
against the beSecurityDescription schema. The default is
"false". Valid values are "true" or
"false".</comment>
</param>
</module>
<module role="org.fcrepo.server.storage.DOManager" class="org.fcrepo.server.storage.DefaultDOManager">
<comment>The interface to the storage subsystem. This provides
context-appropriate DOReaders and DOWriters for reflecting on and
writing to the objects stored in the repository. It also provides
methods for reflecting on the contents of the repository as a whole.</comment>
<param name="defaultDCControlGroup" value="X">
<comment>The control group to use for the system-generated DC datastream
if no DC datastream is present on ingest. Must be "X" or "M".</comment>
</param>
<param name="gSearchPassword" value="examplePassword">
<comment>The associated password for accessing the REST endpoint
of the Fedora Generic Search service. This parameter is only
required if GSearchDOManager is used, and the service requires
authentication.</comment>
</param>
<param name="storageCharacterEncoding" value="UTF-8">
<comment>If the serialization format is text-based, this is the
character encoding that should be used. Default is UTF-8.</comment>
</param>
<param name="gSearchUsername" value="exampleUsername">
<comment>The username for accessing the REST endpoint of the
Fedora Generic Search service. This parameter is only required if
GSearchDOManager is used, and the service requires
authentication.</comment>
</param>
<param name="storagePool" value="localMySQLPool">
<comment>The named connection pool from which read/write database
connections are to be provided for the storage subsystem (see the
ConnectionPoolManager module). Default is the default provided by the
ConnectionPoolManager.</comment>
</param>
<param name="gSearchRESTURL" value="http://localhost:8080/fedoragsearch/rest">
<comment>The REST endpoint of the Fedora Generic Search service.
This parameter is only required if GSearchDOManager is
used.</comment>

```